

China

L/C,D/P,T/T

Disposable Syringe Filter Hydrophobic PTFE Orange 13mm 0.45um 100pcs/pack 3 years

Basic Information

- Place of Origin:
- Certification: CE ISO
- Model Number: 0.22µm 13mm
- Minimum Order Quantity: 100,000pcs
- Delivery Time: Within 15 working days after confirming the order
- Payment Terms:



Product Specification

- Model NO.:
- Outer Diameter:
- Pore Size:
- Media Material:
- Transport Package:
- Specification:
- HS Code:
- Production Capacity:
- Customization:

Sryinge Filter 13mm 0.22µm PTFE 100PCS Epr Box, 50box Per Carton Regular Size + Custom Service 8421299090 500000pcs/month Available | Customized Request



More Images



Product Description

| SKU | Material | Color | Diameter (mm) | Pore Size (µm) | Packagin g | Shelf Life |
|---|------------------------------|------------|------------------|-------------------|--|----------------|
| HN2500 1 | PES | Blue | 13 | 0.45 | 100pcs/pa ck | 3 years |
| HN2500 2 | PES | Yellow | 13 | 0.22 | 100pcs/pa ck | 3 years |
| HN2500 3 | Nylon | White | 13 | 0.45 | 100pcs/pa ck | 3 years |
| HN2500 4 | Nylon | Green | 13 | 0.22 | 100pcs/pa ck | 3 years |
| HN2500 5 | Hydrophobic PTFE | Orange | 13 | 0.45 | 100pcs/pa ck | 3 years |
| HN2500 6 | Hydrophobic PTFE | Purple | 13 | 0.22 | 100pcs/pa ck | 3 years |
| HN2500 7 | Hydrophobic PVDF | Red | 13 | 0.45 | 100pcs/pa ck | 3 years |
| HN2500 8 | Hydrophobic PVDF | Black | 13 | 0.22 | 100pcs/pa ck | 3 years |
| HN2500 9 | PES | Blue | 25 | 0.45 | 100pcs/pa ck | 3 years |
| HN2501 0 | PES | Yellow | 25 | 0.22 | 100pcs/pa ck | 3 years |
| HN2501 1 | Nylon | White | 25 | 0.45 | 100pcs/pa ck | 3 years |
| HN2501 2 | Nylon | Green | 25 | 0.22 | 100pcs/pa ck | 3 years |
| HN2501 3 | Hydrophobic PTFE | Orange | 25 | 0.45 | 100pcs/pa ck | 3 years |
| HN2501 4 | Hydrophobic PTFE | Purple | 25 | 0.22 | 100pcs/pa ck | 3 years |
| HN2501 5 | Hydrophobic PVDF | Red | 25 | 0.45 | 100pcs/pa ck | 3 years |
| HN2501 6 | Hydrophobic PVDF | Black | 25 | 0.22 | 100pcs/pa ck | 3 years |
| HN2501 7 | PP | Light blue | 13 | 0.45 | 100pcs/pa ck | 3 years |
| HN2501 8 | PP | Dark green | 13 | 0.22 | 100pcs/pa ck | 3 years |
| HN2501 9 | PP | Light blue | 25 | 0.45 | 100pcs/pa ck | 3 years |
| HN2502 0 | PP | Dark green | 25 | 0.22 | 100pcs/pa ck | 3 years |
| HN2502 1 | Medium-speed filter paper | - | 25 | - | 100pcs/pa ck | 3 years |
| HN2502 2 | MCE | White | 25 | 0.8 | 100pcs/pa ck | 3 years |
| HN2502 3 | MCE | White | 13 | 0.45 | 100pcs/pa ck | 3 years |
| HN2502 4 | MCE | White | 13 | 0.22 | 100pcs/pa ck | 3 years |
| HN2502 1 HN2502 2 HN2502 3 HN2502 | paper MCE MCE | White | 25 13 | 0.45 | 100pcs/pa ck 100pcs/pa ck 100pcs/pa ck 100pcs/pa | 3 yea 3 yea |

Material Characteristics

- Polyethersulfone (PES): Hydrophilic membrane with high flow rate, high flux, low protein adsorption rate and low elution. It is used to remove fine particles, bacteria, viruses and fungi from aqueous solutions. Generally, it can withstand a pH range of 3 12.
- Nylon: It has good chemical stability, flexibility, is durable and not easy to tear. It can withstand autoclaving at 121°C and is suitable for filtering aqueous solutions and most organic solvents, such as water filtration in electronics, microelectronics and semiconductor industries, tissue culture medium filtration, pharmaceutical solution filtration, beverage filtration and high purity chemical product filtration. Generally, it can withstand a pH range of 3 14.
- Hydrophobic PTFE: It has the broadest solvent compatibility, excellent particle retention performance, and can withstand various sterilization conditions. It is suitable for both liquid and gas filtration. Generally, it can withstand a pH range of 1 14.
- Hydrophobic PVDF: The membrane has high mechanical strength and high tensile strength, with good heat resistance and chemical stability. However, it is not resistant to solvents such as DMSO, THF, etc. It is suitable for gas and steam filtration, as well as filtration of high temperature liquids. Generally, it can withstand a pH range of 2 13.
- Polypropylene (PP): It has high impact resistance, strong mechanical properties and is resistant to a variety of organic solvents and acid base corrosion. Except for being corroded by concentrated sulfuric acid and concentrated nitric acid, it is relatively stable to other chemical reagents.
- Medium speed filter paper: It is used for the detection of metal ions after urine filtration.
- Mixed Cellulose Ester (MCE): It has good hydrophilicity, high porosity and high filtration speed. It is mainly used for: 1) Sterile filtration in





